BJELIN

# Woodura Planks 3.0

## SMEDSTORP 3.0 XXL

Type of wood
Ash

Grading
Select

Surface finishing
Pro matt lacquer

Staining
Earth Grey

Pattern
Plank

Water resistance
High

Smedstorp is a toned-down matt-lacquered hardened wood floor made from ash. Effortless and stylish, this floor in the Earth Grey colour has been paired with the Select grading to provide a clean and harmonious appearance. Smedstorp is a class 33 product, which means it's extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.

## Specification

| GENERAL | |
|---|---|
| Type of floor | **Hardened wood** |
| Type of wood | **Ash** |
| Grading | **Select** |
| Surface finishing | **Pro matt lacquer** |
| Staining | **Earth Grey** |
| Light/dark | **Light** |
| Pattern | **Plank** |
| Locking system | **Välinge 5G® Dry™** |
| Core | **HDF** |

| DIMENSIONS | |
|---|---|
| Format | **XXL** |
| Width | **271 mm** |
| Width (ISO 24337) | **10.7”** |
| Length | **2378 mm** |
| Length (ISO 24337) | **93.6”** |
| Thickness | **11 mm** |
| Thickness (ASTM F387) | **0.43”** |
| Thickness of wear layer | **0,6 mm** |
| Thickness of wear layer (ASTM F410) | **0.02”** |
| Weight per m² | **24 lbs** |

| PACKAGE | |
|---|---|
| Quantity in box | **3 pcs** |
| m² / box | **1,9 m²** |
| sq.ft per box | **20.81 sqft** |
| m² per pallet | **93 m²** |
| sq.ft per pallet | **999 sqft** |
| Weight per m² | **11 kg** |
| Weight per box | **22 kg** |
| Weight per box | **47.8 lbs** |

| CLASSIFICATION AND SAFETY | |
|---|---|
| Supports Underfloor Heating | **Yes** |
| Water resistance | **High** |
| Fire Resistance (EN 13501) | **Cfl-s1** |
| Thermal conductivity (EN 12664) | **0,16 W/(m*K)** |
| Thermal resistance (EN 12667) | **0.07 m²K/W** |
| Formaldehyde emission (EN 717-1) | **E1 <=0.1 ppm (typical value <= 0.05 ppm)** |
| Brinell hardness (EN 1534) | **10 HB (average value)** |
| Impact resistance (EN 14354) | **EC3** |
| Thickness swelling (EN 14354) | **<10% (5% typical)** |
| Wear resistance (EN 14354) | **> 6000 cycles** |
| Slip resistance (USRV) (CEN//TS 15676) | **40** |
| FSC | **FSC Mix** |
| Greenguard Gold | **Greenguard Gold Certified** |
| CE Marked | **Yes** |
| Limited warranty (public environment) | **10 years** |
| Limited warranty (home environment) | **Limited Lifetime Warranty** |
| Level of use domestic (EN ISO 10874) | **Class heavy Residential (Class 23)** |
| Level of use commercial (EN ISO 10874) | **Class heavy commercial (Class 33)** |

**Bjelin Sweden AB** bjelin.com support@bjelin.se +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.

*For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.*